



Improving your PERFORMANCE

323Du/MC8 Low-flow RS232/analogue/manual control microcassette pumps

Caratteristiche

- RS232 serial communication
- High-performance microprocessor controlled pumps
- Flow rates from 2µl/min to 36ml/min per channel
- Precision digital speed control 1rpm steps from 3 to 110rpm
- Fitted with lower-pulsing 318MC eight-roller 5 channel microcassette pumphead
- Add one snap-fit 318MCX extension pumphead for ten channels of flow
- Digital TTL or remote switch inputs for run/stop and direction
- Rear panel 25D socket accepts analogue auto-control signal input for speed control 4-20mA, 0-10V
- High visibility digital display and keypad lock
- Compact design, chemical resistant case, contemporary styling
- Zero maintenance, quiet brushless DC motor
- MemoDose facility for accurate single shot dosing
- Auto-restart for mains failure recovery and timer control
- Uses colour coded, double segment manifold tubing



323Du/MC8




323Du/MC8 + 318MCX



Portate (ml/min)

Codice colore	Arancio/ Nero	Arancio/ Rosso	Arancio/ Blu	Arancio/ Verde	Arancio/ Giallo	Arancio/ Bianco	Nero/ Nero	Arancio/ Arancio	Bianco/ Bianco	Rosso/ Rosso	Grigio/ Grigio	Giallo/ Giallo	Giallo/ Blu
Diametro mm	0.13	0.19	0.25	0.38	0.50	0.63	0.76	0.88	1.02	1.14	1.29	1.42	1.52
3.0rpm	0.002	0.01	0.01	0.02	0.04	0.07	0.11	0.14	0.18	0.24	0.27	0.33	0.38
110rpm	0.09	0.3	0.5	0.8	1.4	2.6	3.9	5.3	6.6	8.8	10	12	14

Codice colore	Blu/ Blu	Verde/ Verde	Viola/ Viola	Viola/ Nero	Viola/ Arancio	Viola/ Bianco
Diametro mm	1.65	1.85	2.05	2.29	2.54	2.79
3.0rpm	0.46	0.55	0.65	0.79	0.90	0.98
110rpm	17	20	24	29	33	36



323Du/MC8 Low-pulse RS232/analogue/ manual control microcassette pumps

Codici		
323Du 3.0-400rpm	drive only	036.3154.000*
318MC	eight roller five channel pumphead	033.6853.000
318MCX	eight roller five channel extension pumphead	033.6854.000

*Sostituire l'ultimo 0 con **A, E o U** per rete elettrica **americana, europea o britannica**

Tubo				
Tubo Manifold per teste 318MC				
Codice colore	Dia. (mm)	Marpren* [*]	PVC	Silicone
Arancio/Nero	0.13		981.0013.000	
Arancio/Rosso	0.19		981.0019.000	
Arancio/Blu	0.25	979.0025.000	981.0025.000	
Arancio/Verde	0.38	979.0038.000	981.0038.000	
Arancio/Giallo	0.50	979.0050.000	981.0050.000	
Arancio/Bianco	0.63	979.0063.000	981.0063.000	983.0063.000
Nero/Nero	0.76	979.0076.000	981.0076.000	983.0076.000
Arancio/Arancio	0.88	979.0088.000	981.0088.000	983.0088.000
Bianco/Bianco	1.02	979.0102.000	981.0102.000	983.0102.000
Rosso/Rosso	1.14	979.0114.000	981.0114.000	983.0114.000
Grigio/Grigio	1.29	979.0129.000	981.0129.000	983.0129.000
Giallo/Giallo	1.42	979.0142.000	981.0142.000	983.0142.000
Giallo/Blu	1.52	979.0152.000	981.0152.000	983.0152.000
Blu/Blu	1.65	979.0165.000	981.0165.000	983.0165.000
Verde/Verde	1.85	979.0185.000	981.0185.000	983.0185.000
Viola/Viola	2.05	979.0205.000	981.0205.000	983.0205.000
Viola/Nero	2.29	979.0229.000	981.0229.000	983.0229.000
Viola/Arancio	2.54	979.0254.000	981.0254.000	983.0254.000
Viola/Bianco	2.79	979.0279.000	981.0279.000	983.0279.000

* For autoclavable Marprene tubing, please replace last "0" with "*" - for example 979.0238.00*
Please state the product code when ordering pumps and tubing

Specifiche

Peso	5.0kg
Temperatura lavoro	5°C to 40°C
Massima rumorosità	<70dBA at 1m
Rapporto	133:1
Standards	CE, BS0800, IEC335-1, EN60529 (IP31)
Alimentazione	1ph, 100-120V, 220-240V 50/60Hz, 100VA

Testa

Drive	
Drive base	Powder coated aluminium casework
Drive top	Self-coloured ABS plastic
Pumphead	
Cassettes	Acetal copolymer-Kematal (PVDF optional)
Fixings	Stainless steel pins
Mounting plate, front and rear	Glass filled Nylon
Pumphead cradle	Aluminium extrusion, anodised
Rollers	MoS2 filled Nylon 6 (Nylatron)
Rotor spindle carriers	Machined aluminium
Spindles	Stainless steel
Fixings	Stainless steel
Sealed bearings	Carbon steel



Watson-Marlow-Bredel Pumps
Falmouth
Cornwall
England
TR11 4RU
Tel: +44 (0) 1326 370370
Fax: +44 (0) 1326 376009
www.watson-marlow.com
Email support4gb@watson-marlow.co.uk